

Republic of the Philippines EPARTMENT OF PUBLIC WORKS AND HIGHWAYS

BILIRAN DISTRICT ENGINEERING OFFICE

REGIONAL OFFICE VIII Naval, Province of Biliran

| Name of Procuring Entity: DPWH-BDEO | | Purchase Request (P.R. No.): | 2024 - 11 - 0187 | | |
|-------------------------------------|--------------------------|--------------------------------------|------------------|--|--|
| Revised on | 1 | Date : | 11 - 28 - 2024 | | |
| Standard Form/Title | : REQUEST FOR Q UOTATION | Office/End-User: Maintenance Section | | | |
| COMPANY NAME | : | | | | |
| ADDRESS | 1 | | | | |
| TEL NOVEAU NO | | TIN . | | | |

Please quote your lowest price on the item(s) listed below, subject to the Terms and Conditions set herein and submit to the BAC Secretariat for Gods your Quotation duly signed by you or your authorized representative prior closing time at 09:00 A.M on 2 1 DEC opening of Bid will follow on the same day

TERMS and CONDITIONS

- 1. All entries must be typewritten or legibly written.
- 2. Delivery period within 30 Calendar days upon receipt of the approved funded Purchase Order (PO). Administrative penalties pursuant to Sec. 69 of the Revised IRR-RA 9184 shall be imposed for non-delivery without valid reason.
- 3. Warranty shall be for a minimum of three (3) months for supplies & materials:
- 4. One year for Equipment from date of acceptance by the end user. (Three years for IT Equipment)
- 5. Price validity shall be for a period of sixty (60) calendar days.
- 6. G-EPS Registration Certificate/Mayor's Permit /Tax Clearance / SPA / Company ID / Orgazitional chart / DTI / BIR Certificate of registration (COR) / ITR (if above 500 thousand approve ABC) shall be attached upon Submission of the quotation.
- 7. Statement of the prospective bidder that is not blacklisted or barred from bidding by the Government or any of its agencies, office, corporations or LGU (Sec.25 .2.iv.1,R-IRR of RA No. 9184;9.2,COA Cir.2012-001)
- 8. Sworn affidavit of the bidder that it is not related to the head of the Procuring Entity (HOPE) by consanguinity or affinity up to the third civil degree (Sec. 47, R-IRR of RA 9184; 9.2,COA Cir.2012-001)
- 9. Bidders shall submit original brochures showing certifications of the product.
- 10. Please indicate the brand for each items being offered.
- 11. The approved budget ceiling for this procurement is

P710,000.00

12. To be delivered at DPWH, BDEO COMPOUND

| Inclination accuracy ± 1° Min range: ≥ 5YD/M Max range: ≥ 650m Measuring accuracy: ± 0.2 °C Measuring resolution + 0.1YD/M Measuring resolution + 0.1YD/M Measuring resolution + 0.1YD/M Measuring resolution + 0.1YD/M Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Measuring accuracy: ± 0.2 °C Measuring arge up to ≥ 150m Dust and splash protection: IP 54 | QTY | UNIT | UNIT PRICE | TOTAL PRICE |
|--|-----|------|------------|-------------|
| Engine Made in Japan, w/ Complete Accessories must have serial number engrave in the engine (Good Quality) 2 Safety Rubber Boots 3 Construction Gloves 4 Laser Range Finder 650m/1200m Measuring accuracy: +/-1YD/M Magnification: ≥ 6x Measuring resolution +/-0.1YD/M Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | 15 | Unit | | |
| Accessories must have serial number engrave in the engine (Good Quality) 2 Safety Rubber Boots 3 Construction Gloves 4 Laser Range Finder 650m/1200m Measuring accuracy: +/-1YD/M Magnification: ≥ 6x Measuring resolution +/-0.1YD/M Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°-85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| 2 Safety Rubber Boots 3 Construction Gloves 4 Laser Range Finder 650m/1200m Measuring accuracy: +/-1YD/M Magnification: ≥ 6x Measuring resolution +/-0.1YD/M Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| 2 Safety Rubber Boots 3 Construction Gloves 4 Laser Range Finder 650m/1200m Measuring accuracy: +/-1YD/M Magnification: ≥ 6x Measuring resolution +/-0.1YD/M Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| 4 Laser Range Finder 650m/1200m Measuring accuracy: +/-1YD/M Magnification: ≥ 6x Measuring resolution +/-0.1YD/M Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | 100 | Pair | | |
| 650m/1200m Measuring accuracy: +/-1YD/M Magnification: ≥ 6x Measuring resolution +/-0.1YD/M Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | 100 | Pair | | |
| 650m/1200m Measuring accuracy: +/-1YD/M Magnification: ≥ 6x Measuring resolution +/-0.1YD/M Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | 1 | Unit | | |
| Object diameter: ≥ 20mm Range acquisition time: ≥ 0.3-0.8s Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| Eye relief: ≥ 17 mm Inclination range: + 85°85° FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| FOV: 6° Inclination accuracy ± 1° Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| Min range: ≥ 5YD/M Display type: LCD Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| Max range: ≥ 650m Power source: Built-in lithium battery Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | 14 | | |
| Weight: 190g Dimension: ≥ 40*73*106MM 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| 5 Laser Measure Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| Measuring accuracy: ± 0.2 °C Digital view finder: integrated Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| Automatic deactivation: 0 min Supported android devices: Smartphone Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | 1 | Unit | | |
| Weight, approx.: 0.23 kg with android 4.3 or higher Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | - | | | |
| Memory capacity (values): ≥ 50 Measuring range up to ≥ 150m Dust and splash protection: IP 54 | | | | |
| Dust and splash protection: IP 54 | | | | |
| | | | | |
| - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 | | | | |
| Tripod thread: 1/4" | | | | |
| X-X-X-X-X-X-X | | | | |

The awarding for this RFQ will be on lump-sum basis. Prospective Suppliers must quote for all the items. Otherwise they will be subjected for disqualification. Brand and Model Warranty Delivery Period Price Validity After having carefully read and accepted your General Conditions, I/We quote you on the item(s) at prices noted above. If the space for Delivery Period, Warranty and Price Validity are left blank, it means that I concur with the Terms and Conditions specified by DPWH.

| | Printed Name/Signature/Date |
|---|---------------------------------------|
| - | Tel. No./Cellphone No./E-mail Address |

(BAC, Chairperson)