

REPUBLIC OF THE PHILIPPINES DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS

REGIONAL OFFICE X
MISAMIS OCCIDENTAL 1st DISTRICT ENGINEERING OFFICE
OROQUIETA CITY, MISAMIS OCCIDENTAL

C.Y. 2025 PROJECT
DETAILED ENGINEERING DESIGN PLAN FOR

CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, ALTRADE, ALORAN, MISAMIS OCCIDENTAL

GPS LOCATION:

8.412892° N

123.823° E

SUBMITTED:

NOLLY S. BOLANDO CHIEF, PLANNING AND DESIGN SECTION RECOMMENDED:

OIC-ASSIST ANT DISTRICT ENGINEER

APPROVED:

CHARITO B. MADULA DISTRICT ENGINEER

G. GENERAL DRAWING & SUMMARY OF QUANTITIES CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, ALTRADE, ALORAN, MISAMIS OCCIDENTAL

	SUMMARY OF QUANTITIES			
ITEM NO.	DESCRIPTION	QUANTITY	UNIT	REMARKS
PART A	FACILITIES FOR THE ENGINEER		***************************************	
A.1.1(8)	PROVISION OF FIELD OFFICES FOR THE ENGINEER (RENTAL BASIS)	4.00	Month	T
PART B	OTHER GENERAL REQUIREMENTS			
B.3 (1)	PERMITS AND CLEARANCE	1.00	Lump Sum	
B.5 (1)	PROJECT BILLBOARD/SIGNBOARD	1.00	Each	
B.7 (1)	OCCUPATIONAL SAFETY AND HEALTH	1.00	Lump Sum	
DIVISION I	CIVIL WORKS	183		
PART C	EARTHWORKS			
801(1)	REMOVAL OF STRUCTURES AND OBSTRUCTION	1.00	Lump Sum	T
803(1)a	STRUCTURE EXCAVATION, COMMON SOIL	43.95	Cu.m.	
804(7)	EMBANKMENT FROM ROADWAY/ STRUCTURE EXCAVATION, COMMON SOIL	32.83	Cu.m.	
804(7)	GRAVEL FILL	5.98	Cu.m.	
PART D	REINFORCED CONCRETE			2
900(1)c	STRUCTURAL CONCRETE, 3000 psi, CLASS A, 28 DAYS	2.29	Cu.m.	
902(1)d	STRUCTURAL CONCRETE, 4000 psi, CLASS A, 28 DAYS	23.99	Cu.m.	
902(1)a1	REINFORCING STEEL (DEFORMED), GRADE 40	5088.82	Kg.	
903(2)a1	FORMWORKS AND FALSEWORKS	132.82	Sq.m.	1,7(23,125)
PART E	FINISHING AND OTHER CIVIL WORKS			
1001(8)	SEWER LINE WORKS	1.00	Lump Sum	
1001(9)	STORM DRAINAGE AND DOWNSPOUT	1.00	Lump Sum	
1001(11)	SEPTIC VAULT/TANK, CONCRETE/CHB	1.00	Lump Sum	
1002(4)	PLUMBING FIXTURES	1.00	Lump Sum	
1003(1)e2	CEILING, METAL FRAME, PREPAINTED METAL	59.16	Sq.m.	
1004(2)	FINISHING HARDWARE	1.00	Lump Sum	
1007(1)b	ALUMINUM FRAMED GLASS DOOR, SWING TYPE	9.56	Sq.m.	
1008(1)c	ALUMINUM GLASS WINDOW, AWNING TYPE	1.38	Sq.m.	5500
1008(1)d	ALUMINUM GLASS WINDOW, FIXED TYPE	13.80	Sq.m.	
1010(1)	FRAMES (JAMBS, SILLS, HEAD, TRANSOMS AND MULLION)	7.00	Set	
1010(2)b	DOORS, WOOD PANEL	10.50	Sq.m.	
1013(2)b	FABRICATED METAL ROOFING ACCESSORY, GAUGE 26 (0.551 mm), FLASHING	32.80	L.m.	
1013(2)c	FABRICATED METAL ROOFING ACCESSORY, GAUGE 24 (0.701 mm), GUTTERS	16.80	L.m.	
1014(1)a2	PRE-PAINTED METAL SHEETS, ABOVE 0.427mm, CORRUGATED, LONG SPAN	214.00	Sq.m.	
1018(4)	SYNTHETIC GRANITE TILES	395.68	Sq.m.	
1019(2)c	WOOD TILE, WALLS, OTHER	21.60	Sq.m.	
1019(3)c	WOOD TILE, CEILING, OTHER	116.78	Sq.m.	
1027(1)	CEMENT PLASTER FINISH	314.48	Sq.m.	
1032(1)a	PAINTING WORKS, MASONRY/CONCRETE	718.67	Sq.m.	
1032(1)c	PAINTING WORKS, STEEL	718.67	Sq.m.	
1033(1)	METAL DECK PANEL	31.38	Sq.m.	

SCOPE OF WORKS:

ELECTRICAL

MECHANICAL

1039(1)

1046(2)a1

1046(2)a2

1047(1)

1047(4)a

1047(4)b

1047(5)b

1047(5)c

1047(5)d

1047(8)a

1047(8)b

1051(1)a

1100(10)

1101(33)

1102(1)

1103(1)

1200(13)a

PART G

PART F

REMOVAL OF STRUCTURES AND OBSTRUCTIONS

ALUMINUM CLADDING

CHB NON-LOAD BEARING (INCLUDING REINFORCING STEEL), 100mm THICK

CHB NON-LOAD BEARING (INCLUDING REINFORCING STEEL), 150mm THICK

METAL STRUCTURES

METAL STRUCTURAL ACCESSORIES, BOLTS AND RODS

METAL STRUCTURAL ACCESSORIES, TURNBUCKLE

METAL STRUCTURAL ACCESSORIES SAGRODS

METAL STRUCTURAL ACCESSORIES, CROSS BRACING

METAL STRUCTURAL ACCESSORIES, STEEL PLATES

STRUCTURAL STEEL, TRUSSES

STRUCTURAL STEEL, PURLINS

RAILING

CONDUIT, BOXES & FITTINGS (CONDUIT WORKS/CONDUIT ROUGH-IN)

WIRES AND WIRING DEVICES

PANELBOARD WITH MAIN & BRANCH BREAKERS

LIGHTING FIXTURES

AIR CONDITIONING SYSTEM

73.95

66.94

3146.04

40.00

71.64

160.99

280.64

705.60

1.00

1.00

1.00

1.00

Sq.m.

Sq.m.

Sq.m.

Kg.

Each

Fach

Kg.

Kg.

Kg.

Kg.

Kg.

Lump Sum

Lump Sum


Lump Sum

Lump Sum Lump Sum

Lump Sum

- EXCAVATION FOR FOUNDATION (11 UNITS)
- EMBANKMENT FROM ROADWAY
- CONSTRUCTION OF SEPTIC TANK
- INSTALLATION OF SEWER LINE AND COLD WATER LINE
- CONSTRUCTION OF REINFORCED CONCRETE FOOTINGS AND WALL FOOTING
- CONSTRUCTION OF REINFORCED CONCRETE 11-UNIT COLUMNS, BEAM AND CANTILEVER BEAM
- CONSTRUCTION OF FIREWALL
- INSTALLATION OF TILES
- REPLACEMENT AND CONSTRUCTION OF TRUSSES AND ROOFING WORKS
- INSTALLATION OF ALUMINUM METAL CLADDING WITH FRAME ON BUILDING FACADE
- FINISHING HARDWARE
- WINDOW ACCESSORY
- CEMENT PLASTER FINISH AND PAINTING WORKS
- ELECTRICAL WORKS

NOTES: QUANTITIES SHALL BE VERIFIED DURING ACTUAL CONSTRUCTION



CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, ALTRADE, ALORAN, MISAMIS OCCIDENTAL

SUMMARY OF QUANTITIES SCOPE OF WORK DARY 3. TOLEDO ARCHITECT II HOPEAN S.PUTIS
CHIEF PLANNING AND
DOOR


NOLLY S. BOLANDO
PLANNING AND DESIGN SECTION
DATE:

CHARITO B. MADULA
DISTRICT EN GINEER
DATE:

PDS - MISOCC1ST

G


01 03



Legend Liquefaction Susceptibility				
	Prone			
	Provincial boundary			
printerioral and comments	Municipal boundary			
	Road / Highway			
	Built-up area / settlement			
A11	River / Stream			

LEGEND:

HAZARD	ASSESSMENT	EXPLANATION AND RECOMMENDATION
Ground Rupture	Safe; Approximately 34 km north of the Tangub Fault	Active faults are faults that have moved within the last 10,000 years. An active fault may show evidence or may have documented history of recent movements. Ground rupture is a displacement along an active fault trace that reaches the surface.
Stoom napeure		Ground rupture hazard assessment is the distance to the nearest known active fault. The recommended buffer zone, or Zone of Avoidance, against ground rupture hazard is at least 5 meters on both sides of the active fault or from its zone of deformation.
Ground Shaking	Prone	All sites may be affected by ground shaking in the event of an earthquake and can be mitigated by following the provisions of the National Building code and the Structural code of the Philippines.
Liquefaction	Safe	Liquefaction is a phenomenon wherein the ground, especially near the river, lake and coasts, behaves like liquid similar to quicksand due to very strong shaking.
Earthquake-Induced Landslide	Data are being updated	Earthquake-induced landslides are the downward slope movement of rocks, solid and other debris commonly triggered by strong shaking.
Tsunami	Safe	A tsunami is a series of sea waves commonly generated by under the sea earthquakes.



O2 ACTIVE FAULT MAP
NOT TO SCALE

REPUBLIC OF THE PHILIPPINES DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS REGIONAL OFFICE X MISAMIS OCCIDENTAL 1st DISTRICT ENGINEERING OFFICE OROQUIETA CITY, MISAMIS OCCIDENTAL

PROJECT NAME AND LOCATION: SHEET CONTENTS: CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, ALTRADE, ALORAN, MISAMIS OCCIDENTAL LIQUEFACTION MAP OF MISAMIS OCCIDENTAL ACTIVE FAULT MAP ALORAN, MISAMIS OCCIDENTAL

NOLLY S. BOLANDO CHIEF, PLANNING AND DESIGN SECTION

REY M. ROA

OIC-ASSISTANT DISTRICT ENGINEER

CHARITO B. MADULA DISTRICT ENGINEER

G 02 03

