

Republic of the Philippines
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS
BUKIDNON 2ND DISTRICT ENGINEERING OFFICE
Don Carlos, Bukidnon, Region X

| | | |
|---------------------------------------------------|--|---------------------------------------|
| Name of Procuring Entity : DPWH-BUKIDNON 2ND DEO | | Request for Quotation : 2024-12-0505 |
| Revised on : | | : December 4, 2024 |
| Standard Form/Title : REQUEST FOR QUOTATION | | Office/End-User : Maintenance Section |
| COMPANY NAME : | | |
| ADDRESS : | | |
| TEL. NO./FAX No. : | | |
| Please quote your lowest price on the item stated | | TIN : |

Please quote your lowest price on the item(s) listed below, subject to the Terms and Conditions stated below and submit your quotation duly signed by your representative not later than 10:00 A.M. of December 13, 2024 in the return envelope attached herewith, to the BAC Secretariat, DPWH-Bukidnon.

TERMS AND CONDITIONS

1. All entries must be typewritten or legibly written.
2. Delivery period within **10 working days** upon receipt of the approved funded Purchase Order (P.O). Administrative penalties pursuant to Sec. 69 of the Revised IRR-RA 9184 shall be imposed for non-delivery without valid reason.
3. Warranty shall be for a minimum of three (3) months for supplies & materials; one year for equipment, 3 years for IT equipment from date of acceptance by the end-user.
4. Price Validity shall be for a period of sixty (60) calendar days.
5. Documents required to be submitted with the bid:
 - 5.1 **Certified copy of PhilGEPS Registration;**
 - 5.2 **Certified copy of Mayor's Permit/Business Permit**
 - 5.3 **Geotagged Photo of Physical Store/Establishment.**
 - 5.4 **Notarized Omnibus Sworn Statement**
6. Bidders shall submit original brochures showing certification of the product.
7. Please indicate the brand for each items being offered.
8. The approved budget ceiling for this procurement is Php 285,175.00
9. For Corporation please provide Secretary Certificate and Board Resolution.
10. FOB: DPWH Compound

~~MARIO S. CALLAO~~

Chief, Administrative Section
Vice Chairperson, BAC

The awarding for this RFQ will be on lump-sum basis. Prospective Suppliers must quote for all the items. Otherwise they will be subjected for disqualification

[illegible][illegible]**Delivery Period**

Warranty

Price Validity

After having carefully read and accepted your General Conditions, I / We quote you on the item(s) at prices note above. If the space for Delivery Period, Warranty and Price Validity are left blank, it means that I concur with the Terms and Conditions specified by DPWH.

Printed Name / Signature / Date

Tel. No. / Cellphone No. / E-mail Address

Latex Paint

Technical Data:

| | |
|----------------------------|-------------------------------------------------------------------------------------------------|
| Principal Uses | It is ideal for interior and exterior surfaces such as concrete, bricks, plaster, and drywalls. |
| Vehicle Type | Acrylic |
| Finish | Gloss |
| VOC (± 2.0 g/L) | 12.1 g/L |
| Dry Time | Touch: 1 hour Recoat: 2 hours |
| Density (± 0.05 kg/L) | 1.18 kg/L |
| Theoretical Coverage | 30-35 sq.m. *per 4-Liters at 1.7-1.4 mils DFT |
| Tinting | Latex Colors at a maximum level of ¼ Liter per 4-Liter can |
| Thinning Solvent | Not more than ½ Liter of clean water per 4-Liter can |
| Clean-Up Solvent | Water |
| Packaging | 4-Liters |
| Application | By brush, roller, or airless spray |

Surface Preparation:

| | |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| New Concrete | Allow new concrete to dry for 14-28 days under normal weather conditions before painting. Surface to be painted should be clean and dry, free from oil, grease, dust, dirt, contaminants, and all loose grit and mortar. If neutralizing, treat surface with a solution of 1 part Masonry Neutralizer diluted in 16 parts water, applying liberally by brush or roller. Let dry overnight before rinsing with water to remove white crystals that form on the surface. Let dry before painting. However, if the concrete has been cured for more than 28 days, there is no need for neutralizer. |
| Drywall Substrates | Install and secure joints as per manufacturer's recommendations. |
| Repainting | Scrape off all loose, scaling, flaking, and peeling paint manually or by using Paint and Varnish Remover, as necessary. Wash surfaces clean and completely remove chemical residue. Let it dry. For repainting concrete with chalky old paint, use Chalk Blocker as surface conditioner. In case of mildew infestation, treat with a bleach solution (1:3, laundry bleach to water, respectively) by swabbing or brushing. To ensure proper treatment, let stand for 24 hours before cleaning off residue. Let dry. |

Painting Schedule:

| | |
|-----------------------------------------|-------------------------------------------------------------|
| Primer: | Flat Latex |
| Putty: | Masonry Putty (interior use) Acrytex Cast (exterior use) |
| 2 nd & 3 rd coat: | Latex (any desired sheen and color) |

Prepared by: ,

Jasmin B. Bolinas
Engineer II