

Posting



Republic of the Philippines
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS
LEYTE 4TH DISTRICT ENGINEERING OFFICE
Ormoc City, Region VIII



Name of Procuring Entity : DPWH 4TH DEO		Request for Quotation (P. R. No.): 2025-07-094	
Revised on :		Date: July 30, 2025	
Standard Form/Title : REQUEST FOR QUOTATION		Office/End-User :	
COMPANY NAME :		JOEL V. PEREZ	
ADDRESS :			
TEL. NO. / FAX NO. :			

*Please quote your lowest price or the item(s) listed below, subject to the Terms and Conditions stated below and submit your quotation duly signed by your representative not later than **AUG 05 2025**, 9:00 a.m. in the return envelope attached herewith, to the Procurement Office, DPWH, 4TH DEO, Ormoc City, Leyte.*

TERMS AND CONDITIONS :

- All entries must be typewritten or legibly written.
- All pages must be duly signed.
- Delivery period within 20 C. D. upon receipt of the approved funded Purchase Order (P. O.). Administrative penalties pursuant to Sec. 69 of the Revised IRR-RA 9184 shall be for a minimum for non-delivery without valid reason.
- Warranty shall be for a minimum of three (3) months for supplies & materials: one year for Equipment from date of acceptance by the end-user.
- Price validity shall be for a period of sixty (60) calendar days.
- G-EPIS Registration Number & Mayor's Permit/Business Permit, ITR and Omnibus shall be attached upon submission of the quotation.
- Bidders shall submit original brochures showing certifications of the product if
- Quotations to be submitted by Lot
- Please indicate the brand for each item being offered.
- Eco-friendly supplies/equipment
- The approved budget ceiling for this procurement is **P162,594.00**
- Quotations submitted thru mail & Fax will not be accepted.

Item No.	ITEM / DESCRIPTION	QTY.	UNIT	UNIT PRICE	TOTAL PRICE
1	Ultimate Stainless Welding Electrode (All Types) Mechanic Properties: Tensile strength - 128,000 psi Work Hardened - 186,000 psi Yield Strength - 90,000 psi International Specs - AWS/ASME II C SFA 5.4 Made in USA - ISO 3581	3	Unit		
2	Champering/Cutting Electrode Amperage Setting: Minimum Amperage - 100 Maximum Amperage - 170 Made in USA				
3	Wire Rope Lubricant Spray Properties: Triple Penetration Protective against wear or slides Resistant to sea water Temp range of 30°C to +100°C Net can size 400 ml				
4	Industrial Degreaser, Label Remover Spray Properties: Reliable and Gentle Ph - Neutral Efficient degreaser Removes dirt, grease, oil, etc.				
*****Nothing Follows*****					
Grand Total					

For use in the Maintenance Section charge to AMWP 3rd Additional Fund Utilization.

Brand and Model	Warranty
Delivery Period	Price Validity

After having carefully read and accepted your General Conditions, I / We quote you on the item(s) at price note above. If the space for Delivery Period, Warranty and Price Validity/ are left blank, it means that I concur with the Terms and Conditions specified by DPWH.

Printed Name / Signature / Date

Tel No.: (053) 255-8683
c/o Vanilyn C. Catampatan

Tel. No. / Cellphone No. / E-mail Address