

# Technical Specifications

Item		Statement of Compliance
1	<p><b>MANLIFT TRUCK</b></p> <p><b>SPECIFICATIONS:</b></p> <p><b>ENGINE</b></p> <p><b>DISPLACEMENT</b> : 5.1 LITER/5,100 CC</p> <p><b>OUTPUT</b> : 200 TO 210 HP</p> <p><b>TORQUE</b> : 820 TO 825 N-M</p> <p><b>COMMON RAIL FUEL INJECTION</b> : IN-LINE 4 CYLINDER</p> <p><b>GVW</b> : 14 TONS</p> <p><b>GEARBOX</b> : MANUAL TRANSMISSION, 6 SPEED</p> <p><b>CAB</b> : DAY CAB</p> <p><b>CHASSIS</b> : FRONT-PARABOLIC, 5.0 TONS</p> <p>: REAR-TWO MULTI LEAF DUAL</p> <p>: STAGE, 9.5 TONS</p> <p>: WHEELBASE, 4250MM</p> <p><b>REAR AXILE</b> : SINGLE REDUCTION</p> <p><b>BRAKES</b> : FULL AIR BRAKES WITH ABS AND</p> <p>: EXHAUST BRAKES,</p> <p>: AUTOMATIC SLACK ADJUSTERS</p> <p><b>TIRES AND RIMS</b> : 9.00R20 AND 8 TUDS</p> <p><b>FUEL TANK</b> : 170 TO 190 LITERS</p> <p><b>FEATURES</b> : 170 TO 190 LITERS</p> <p>: WINDOWS, CRUISE CONTROL, AIR</p> <p>: SUSPENDED DRIVER</p> <p>: SEAT, AIR-CONDITIONED CAB</p> <p><b>SUPERSTRUCTURE</b> : BODY BUILDER ELECTRICAL</p> <p>: CENTER, HOLES FOR</p> <p>: BODY ATTACHMENTS</p> <p><b>CRANE, KNUCKLES TYPE 3 TONS</b></p> <p>: FRONT STABILIZER LEGS WITH</p> <p>: MANUAL EXTENTION 3370 MM</p> <p>: CARGO BODY-DIMENSION 4560MM</p> <p>: X 2350MM X 400MM (LXWXH)</p> <p>: 4 HYDRAULIC EXTENSIONS</p> <p>: THEORITICAL LIFFTNG CAPACITY</p> <p>6.53T @ 1M</p> <p>3.225T @ 2.05M</p> <p>1.79T @ 2.05M</p> <p>1.23T @5.2M</p> <p>0.935T @ 6.75M</p> <p>0.690t @ 8.40M</p> <p><b>MANLIFT</b></p> <p>HEIGHT 10-12M</p> <p>LENGTH 9.3M</p> <p>2 MEN FIBERGLASS BASKET WIH</p> <p>INSULATING PLATE,</p> <p>SELF-BALANCED: CAPACITY200KG</p> <p>BASKET SUITABLE 1500-200 VOLTS</p> <p>(CERTIFICATE AVAILABLE)</p> <p>WITH EMERGENCY HAND -PUMP</p> <p><b>EMISSION</b> : EURO 5 EMISSION DIESEL ENGINE</p>	