

Technical Specifications

Item	Specification	Statement of Compliance
		<p>[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]</p>
1	PHOTOCOPIER, COLOR COPIER, SCANNER	
	TECHNICAL SPECIFICATIONS:	
	MAIN UNIT	
	Machine Type: A3 Colour Laser Multifunctional	
	Core Functions: Print (with Ecotapling Finish), Copy, Scan, Send and Optional Fax	
	Control Panel: 7-inch TFT LCD WVGA Color Touch Panel	
	Memory: Standard: 2.0GB RAM	
	Storage: Standard: 64GB eMMC (available space 30GB); Optional: 256GB SSD	
	Interface Connection: Network: Standard: 1000Base-T/ 100Base-TX/ 10Base-T, Wireless LAN (IEEE 802.11 b/g/n); Others: Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1	
	Paper Supply Capacity (A4, 80gsm): Standard: 1,200 sheets (100 sheets Multi-purpose tray, 2 x 550 sheets paper cassette); Maximum: 2,300 sheets (with Cassette Feeding Unit-AW1)	
	Paper Output Capacity (A4, 80gsm): Standard: 250 sheets; Maximum: 645 sheets (with Inner Finisher-L1 and Copy Tray-T2)	
	Supported Media Types: Multi-purpose tray: Thin, Plain, Heavy, Recycled, Coated1, Color, Tracing, Bond, Transparency, Labels, Pre-punched, Letterhead, Envelope, Postcard 1SRA3 is unsupported for Coated (257 to 300 gsm); Upper Cassette: Thin, Plain, Heavy, Recycled, Color, Bond, Transparency, Pre-punched, Letterhead, Envelope, Postcard Envelope Feeder Attachment Kit B (standard) is required except ISO-C5.; Lower Cassette: Thin, Plain, Heavy, Recycled, Color, Bond, Transparency, Pre-punched, Letterhead, Envelope, Postcard Envelope Feeder Attachment Kit A (standard) is required.	
	Supported Media Sizes: Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R; Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm; Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm; Envelopes: COM10 No. 10, Monarch, ISO-C5, DL; Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm	
	Upper Cassette: Standard size: A4, A5, A5R, A6R, B5; Custom size: 105.0 x 148.0 mm to 297.0 x 215.9 mm; Envelopes: ISO-C5	

	Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R; Custom size: 105.0 x 148.0 mm to 304.8 x 457.2 mm; Envelopes: COM10 No. 10, Monarch, DL; Envelope Attachment A (standard) is required	
Item	Specification	Statement of Compliance
	Supported Media Weights: Multi-purpose tray: 52 to 300 gsm1 1SRA3 is unsupported for Coated (257 to 300 gsm); Paper weight supported with Media Adjustment Kit-A1: 60 to 300gsm; Upper/Lower Cassette: 52 to 256 gsm; Duplex: 52 to 220 gsm; Warm-up Time (Quick start mode: ON): 4 Seconds or Less; From Sleep Mode: 10 seconds or less; From Power On: 10 seconds or less; Dimensions (WxDxH): With Platen Cover-Y3: 565 x 659 x 788 mm; With DADF-BA1: 565 x 687 x 891 mm; Installation Space (WxD): 978 x 1,088 mm (with Platen Cover-Y3 + right door & multi-purpose tray opened + paper cassette opened) 1,286 x 1,116 mm (with DADF-BA1 + Inner Finisher-L1 + Copy Tray-T2 extended + paper cassette open)	
	Weight Including Toner: With Platen Cover-Y3: Approx. 71 kg; With DADF-BA1: Approx. 78 kg	
	Print Speed (BW): 1-sided: Up to 26 ppm (A4), Up to 15 ppm (A3), Up to 20 ppm (A4R); Print Resolution (dpi): 600 x 600, 1,200 (half-speed)	
	Page Description Languages: Standard: UFR II, PCL6; Option: Adobe PostScript 3; Direct Print (RUI): PDF, EPS, TIFF/JPEG and XPS; Printing from Mobile and Cloud Applications: AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print	
	Fonts: PS fonts: 136 Roman; PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T) Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts	
	Operating System: UFR II: Windows 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, macOS (10.13 or later); PCL: Windows® 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022; PS: Windows® 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, macOS (10.13 or later); PPD: Windows® 10/11, macOS (10.12 or later); Copy Speed (BW/CL): 1-sided: Up to 26 ppm (A4), Up to 15 ppm (A3), Up to 20 ppm (A4R); First-Copy-Out Time (A4, BW/CL): Approx. 7.0/8.7 seconds or less; Copy Resolution (dpi): 600 x 600; Multiple Copies: Up to 999 copies; Copy Density: Automatic or Manual (9 Levels)	
	Magnification: Variable zoom: 25% to 400% (1% Increments); Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%	

Item	Specification	Statement of Compliance
	Scan Type: Option: Platen Cover-Y3 or DADF-BA1 (2-sided to 2-sided); Document Feeder Paper Capacity (80 gsm): Up to 100 sheets	
	Acceptable Originals and Weights: Platen: Sheet, Book and 3-Dimensioned objects	
	Document Feeder media weight: 1-sided scanning: 38 to 128 gsm (BW), 64 to 128 gsm (CL); 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)	
	Supported Media Sizes: Platen: Max. scanning size: 297.0 x 431.8 mm; Document feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6; Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm	
	Scan Speed (ipm): BW/CL; A4: DADF-BA1; 1-sided Scanning: 70/70 (300 x 300 dpi, send), 51/42 (600 x 600 dpi, copy); 2-sided Scanning: 35/35 (300 x 300 dpi, send), 25.5/25.5 (600 x 600 dpi, copy)	
	Scan Resolution (dpi): Scan for Copy: 600 x 600; Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600; Scan for Fax: 600 x 600; Pull Scan Specifications: Color Network ScanGear2. For both TWAIN and WIA; Supported OS: Windows 10/11/Server 2012/Server 2012 R2/Server 2016/ Server 2019/ Server 2022	
	Send Specifications:	
	Destinations: Standard: E-mail/Inetrnet FAX (SMTP), SMB, FTP, WebDAV; Optional: Super G3 FAX; Address Book: LDAP (2,000) / Local (1,600) / One-touch (200)	
	Send Resolution (dpi): Push: (CL) up to 300 x 300 / (BW) up to 600 x 600; Pull: (CL) up to 300 x 300 / (BW) up to 600 x 600	
	Communication Protocol: FTP: (TCP/IP), WebDAV Email/iFax: SMTP (send), POP3 (receive); Power Source: 220-240V, 50/60Hz, 5A	
	Power Consumption: Maximum: Approx. 1,500W; Sleep Mode: Approx. 0.8W1; 10.8W is not avai;ab;e in all circumstances due to certain settings.	
	Brand and Model: Must be an International Brand Name with existence of at least ten (10) years in the Philippines. It must be in the current catalog and not end-of-life. The Manufacturer's certificate is required, and must be with the original signature, E-signature is not acceptable.	
	Regulatory: ENERGY STAR certified (with Energy Star Stamp). For items that do not carry an Energy Star label, an appropriate means of proof of Energy consumption levels shall be submitted such as technical dossier of the manufacturer or a test report from a recognized body to demonstrate compliance with this requirement.	

Item	Specification	Statement of Compliance
	Documentation and Media: All equipment shall be supplied with the standard manufacturer's documentation, on any electronic storage media and hard copy version where available. Certificate from the Manufacturer that the bidder is an authorized premium partner. Certificate from the Manufacturer that the bidder is an authorized SERVICE PROVIDER partner. Certificate from the Manufacturer that the Machine to be delivered is brand new.	
	Warranty and Maintenance: The Supplier must provide a 3-year warranty for parts and onsite labor from the date of the Inspection and Acceptance Report (IAR) regardless of copy counter. The supplier must also provide a Manufacturer's Certificate as proof of Authorized Dealer or Distributor.	
	Technical Support: Must have a physical store in the region for the local technical support which may include telephobe and e-mail, 8 hours per day (8:00am - 5:00pm) 5 days a week (Monday - Friday) for problem resolution. Support shall have a response time of next business day, free of charge	
	Other Inclusion: Pre-installed toner with additional standard toner per color, cables and connectors.	
xxxxx Nothing Follows xxxxx		

(Signature Over Printed Name of Authorized Representative)

(Designation)

(Name of Bidder/Company)