

Technical Specifications

Quantity	Unit	Item Description	Specifications
1.00	set	Tools Cabinet with tools	Socket Socket Socket (Short, Deep): 1/4" _4-14mm, 3/8" _10-24mm, 1/2" _10-34mm Spark Plug Socket: 1/2" _16-21mm Impact Socket: 3/8" _7-19mm, 1/2" _10-32mm Lug Socket: 17, 19, 21mm Bit Socket: 1/4" _Hex, Torx, Phillips, Flat, 1/2" _Hex External Torx Socket: 3/8" _E5-E16 Triple Square Socket: M6,10,12,14 Adaptor / Universal Joint Adaptor: 1/4"F*3/8M, 3/8"F*1/4M, 3/8"F*1/2M, 1/2"F*3/8M, 3/4"F*1/2M Universal Joint: 1/4", 3/8", 1/2" Wrench Combination: 6-32mm Ratchet Combination: 6-19mm 45-Degree Double Ring: 6-27mm L-Wrench: Hex(1.5mm-10mm), Torx(T10-50), Folding Hex Ratchet / Extension Ratchet: 1/4", 3/8", 1/2" Extension: 1/4 _2", 4" / 3/8" _3", 6", 10" / 1/2" _3", 5", 6" Plier Locking, Circlip(Internal/External), Adjustable, Slip Joint, Needle Nose, Lineman, Cutter Slide Bar / Brake Bar / Speed Handle Brake Bar: 3/8" 1/2" Speed Handle: 1/4", 3/8", 1/2" Screwdriver Screwdriver: Philips Set / Flat Set / Torx Set R achet Screwdriver: 6pcs of bit set Punch/Hammer Punch: Central / Hole / Pin / Flat / Boring Hammer: Soft Face / Ball Peen Scraper: Putty Knife / Scraper 2" Measurement / Power Tool Circuit Tester: 6/12V, LED indicate Gap Gauge: 0.0015"0.025", 25pcs Impact Wrench: Pneumatic_AT5500C Air Ratchet: Pneumatic_AT2610
1.00	set	Vise Grip	Type: Locking Size: 5,6,7,8,9 and 10 inch
1.00	set	Cutter Pliers	Type: Diagonal Size: 5,6,7,8,9 and 10 inch
1.00	set	Pliers	Type: Combination Size: 5,6,7,8,9 and 10 inch
1	set	Torque Wrench	Size: 1/2 " Material: Nickel-Chromium alloy steel
	set	Allen Wrench	Type: Long and Short arm 30 pcs
9	pcs.	Jack Stand	5 Tons
8	pcs.	Jack Stand	2 Tons
2	pcs.	Trouble Light Cordless	Light Bulb Type - LED Plug Type - Type C
3	pcs.	Rubber Mallet	Hammer Head: Rubber Handle Style: Fiberglass Weight: 450 g
2	pcs.	Grease Gun	
1	pc.	Hand Drill	Continuous rating input 450W Capacity Steel: 10 mm (3/8") Wood: 25 mm (1")

			No Load Speed (RPM) 0-3,400
			Dimensions (L x W x H) 228x64x183 mm (9"x2-1/2"x7-1/4")
			Net weight 1.3 kg (2.8 lbs)
			Power supply cord 2.0 m (6.6 ft)
			Chuck capacity: 1.5-10mm (1/6" - 3/8")
			Steel: 10mm (3/8")
			Wood: 25mm (1")
			Input: 450W
			No load speed: 3,000rpm
			Overall length: 228mm (9")
			Net weight: 1.2kg (2.6lbs)
			Power supply cord: 2m (6.6ft.)
1	pc.	Hand Grinder	Power Source - Corded Power
			Input Voltage 220V
			Output: 220V ~ 50/60Hz
			Wheel diameter: 100mm (4")
			Continuous Rating Input: 710W
			No-Load Speed(rpm): 11000r/min
1	pc.	Digital Caliper	Automatic power off
			3-Button LCD
			Stainless Steel
			Two Way measurement (internal and external)
2	pcs.	Air Hose Reel	Material: ABS
			Tube material: PU tube
			Free adjustment: 180°
			Product Size: Length: about 10 meters / 39.37 inches
			Working temperature range: 10° to 50°C
2	pcs.	Heavy Duty Extension	Rated Voltage: 250 V
1	pc.	Battery Charger	Dual charging voltage 12V and 24V
			Electrical device that allows to change lead-acid batteries instantly
			Charger can work in fast charging mode
			Over-load protection
			Current intensity indicator.
			Suitable used in motorcycles, vans, passenger cars, yachts, etc.
1	set	Combination Wrench Set	Size: 6mm-41mm
1	pc.	Air Compressor Vertical	Power : 5.5 Hp
			Watt : 4125
			Air Delivery : 23.6 @ 145 CFM/PSI
			Working Pressure : 145-175 PSI
			Tank Capacity : 200 Liters
			RPM : 900
			Input Voltage : 220V/1ph/60Hz
			Dimension (LxWxH mm) : 972 x 612 x 1310 mm
			Weight : 100 kg
1	pc.	Pressure Gauge with inflator	
1	pc.	Digital Multi Meter	Surge protection 6 kV peak per IEC 61010-1 600 V CAT III, Pollution Degree 2
			Fuse for A input 11 A, 1000 V FAST Fuse (Fluke PN 803293)
			Display Digital: 6,000 counts, updates 4/sec
			Bar graph 33 segments, updates 32/sec
			Operating temperature -10 °C to + 50 °C
			Storage temperature -40 °C to + 60 °C
			Battery 9 volt Alkaline, NEDA 1604A/ IEC 6LR61
			Battery life 400 hours typical, without backlight
1	pc.	Innovated Battery Analyzer	Input voltage 9-16V
			Battery voltage 12 in
			Display LCD display
			Sound signal buzzer
			Working humidity 0-80%
			Dimensions (edit) 205mm x 96mm x 33mm mm
			Backlight automatic
			The weight 380 g
			Working temperature from 0 to 50 ° C deg.
1	pc.	Vacuum	Max. input power 1,250 W
			Weight 9 kg
			Container volume, net 21 l
			Dust class of wet/dry extractor L
			Rated input power 1,250 W
			Container volume, gross 25 l
			Container volume, net, water 15 l
			Dust bag volume, net 20 l
			Dust class L

			Tool dimensions (width) 380 mm
			Tool dimensions (length) 483 mm
			Tool dimensions (height) 453 mm
			Filter surface area 2,300 cm2
			Max. airflow rate (turbine) 65 l/s
			Max. vacuum pressure (turbine) 200 mbar
			Wheels, number 4
1	pc.	AC Clamp Meter Tester	6000 counts
			AC Current: 10mA~400A
			AC Voltage: 1.0~600V
			DC Voltage: 0~600V
			Resistance: 0~6
			Backlight function
			Lower Battery Indication Function
2	set	Heavy Duty Metal Tool Box	18 pcs 1/2" Standard Socket (10-32 mm)
			Ratchet 10"
			Sliding T-Handle 12"
			Flex handle 18"
			Universal joint
			Spark Plug Socket
			Extension Bar
			Offset Extension Bar
			Combination Wrench (6-24mm)
			Hex with Ball Key (1.5-10 mm)
			Philip Head Screwdriver
			Flat Head Screwdriver
			Combination Pliers
			Diagonal Cutting Nipper
			Long Nose Plier
	pc.	Vehicle Scanner	F7S-G, FCAR diagnostic tablet platform, based on Android system,
			built-inWiFi and Bluetooth, supporting powerful diagnostic
			functions, reset and bidirectional special functions diagram wiring,
			remote support and onlineupdate, provides customers with all-in-
			one diagnostic solutions and maintenance service.
	pc.	Tire Changer	Inner Clamping Range inch 12-22
			Outer Clamping Range inch 10-20
			Max. Rim Width inch 12
			Max. Wheel Diameter mm 1000
			Bead Breaking Range mm 90-330
			Dimensions (W x D x H) mm 1040 x 965 x 1490
			Weight kg 200
			Compressed Air Supply bar 8-12
			Power Supply 230V 1ph 50/60 Hz
	pc.	Wheel Balancer	Resolution 1g 1g
			Measuring Speed rpm 200
			Measuring Time sec 6-10
			Rim Width (Dynamic) inch 3"-16"
			Maximum Wheel Width mm 500 (400 w/ wheel guard
			Rim Diameter inch 12"-22"
			Maximum Wheel Diameter mm 1,016 (880 w/ wheel guard)
			Data Entry Manual 1D SAPE
			Maximum Wheel Weight kg 65
			Power Supply 220~240 V, 1 Ph, 50/60 Hz
10	pallet	Trap bags	High-strength, industrial grade polypropylene geotextile fabric
			Height: 2ft
			Width: 30 in
			Depth: 36 in
			Volume: 0.50 yd³
			Filling Volume: 10 yd³
			Filling Weight:13.5 t
10	pallet	Trap bags Double wall	High-strength, industrial grade polypropylene geotextile fabric
			Height: 2ft
			Width: 30 in
			Depth: 36 in
			Volume: 0.50 yd³
			Filling Volume: 10 yd³
			Filling Weight:13.5 t
3	pcs.	Chainsaw	Displacement 71.8cc
			Power 3.3kw
			Max. engine speed with cutting attachment 10000
			rpm Fuel system
			Carburetor All position diaphragm carburetor with

[illegible]